## Residential Field Inspection Checklist

This checklist is intended to be used as a general guide when inspecting new residential construction and contains references applicable to the most common situations. Additional code sections, inspections, or variations to the process may be necessary based on specific conditions.

Footing Inspection	Mechanical Rough-In Inspection	
☐ Site address [R319]	☐ Supply & return ducting [RE403.2.2, RE403.5.6, M603]	
☐ Setbacks to property lines (per local authority)	$\square$ Exhaust fans: bath, kitchen, dryer, insulation	
☐ Soil conditions [R401, R403.1.8]	[RE403.2.1, M501, M504, M505]	
Footings:	Gas Lines: visual, air test, support [M305, FG406,	
☐ Strip or pad footing width, thickness, slope,	FG407, FG408.4]	
strength [R402.2, R403]  ☐ Deck footings [R507.3]	☐ Fireplace: per manufacturer requirements [FG604]	
☐ Depth and frost coverage [R403.1.4]	Electrical Rough-In Inspection	
Rebar: per approved plans if specified	☐ Verify completion by appropriate authority	
Nebali, per approved plans il specifica	The verify completion by appropriate authority	
Foundation Wall: Cast-in-place (pre-	Framing Inspection	
pour) Inspection	☐ Water resistive barrier (House wrap) [R703.2]	
Forms: wall height & thickness [R404.1.3, R404.1.5]	☐ Flashing: drip cap, pan flashing, deck ledger flashing,	
☐ Form placement on footing, footing projections	foundation insulation flashing, other [R703.4, R903.2,	
[R403.1.1]	R507.2.4]  Roof covering: sheathing, venting, step flashing, ice	
☐ Reinforcement: vertical & horizontal rebar [R404.1.3]	barrier [Table R503.2.1.1(1), R803.2, R806, R903.2,	
	R905.1.2]	
Foundation Wall: Block or Cast-in-place	☐ Wall bracing [R602.10]	
(post-pour) Inspection	☐ Wall sheathing [R316.5.12, R602.3, R604]	
☐ Block: thickness, block arrangement [R404.1.2,	☐ Roof truss: bearing, bracing, uplift restraint, fastening,	
R404.1.5]	energy heel [R802.10.3, R802.11, Table RE402.1.1	
☐ Anchor bolt or strap placement and spacing [R403.1.6]	footnote J]  Attic access opening [R807]	
☐ Hold-downs for garage openings [R602.10.6.2]	☐ Outlet in attic for future Radon fan [MN Rules	
☐ Waterproofing [R406.2, RE402.1.1]	1303.2402 Subp. 6]	
☐ Insulation: draining or non-draining (6-mil poly slip	☐ Headers, beams, girders: load path, bearing, size	
sheet required for non-draining) [RE402.1, RE402.2.8]  ☐ Walls braced for backfill [R404.1.7]	[R301.1, R502.6, R602.7]	
☐ Drain Tile: rock base, sock or fabric cover[R405]	☐ Walls: stud height, spacing [R602.3.1]	
	☐ Columns, point loads, blocking: follow load paths	
Plumbing Rough-In Inspection	[R301.1, R407] ☐ Floors (truss, I-joist, lumber): blocking, framing,	
☐ Underground: visual & air test [P Chapter 7, P712.3]	bearing, subfloor [R404.1, R502, R503]	
☐ Above ground: visual & air test [P Chapter 7, P712.3]	☐ Fenestrations: sealing, tempered glazing, fall	
☐ Supply piping: support, hot supplies insulated	protection, U-factor, air leakage [R308, R609, RE402.3,	
[P Chapter 6, P313.3, RE403.4]	RE402.4.3]	
Mixing valves [P408.3]	☐ Smoke & CO alarm locations [R314, R315]	
☐ Tile shower pan [P408.5 – 408.7]	☐ Stairway: rise, run, width, landings, total height	
Slab Inspection/Radon (pre-pour)	[R311.7]  ☐ Headroom clearance [R305.1]	
•	☐ Hallway width [R311.6]	
☐ Gas permeable material (washed rock) [MR 1303.2402] ☐ Soil-gas membrane/6 Mil Poly [MR 1303.2402]	☐ Treated sills and plates, anchorage [R317.1, R403.1.6,	
Radon Tee (or use interior drain tile) [MR 1303.2402]	R404.1, R404.3]	
	☐ Boring & notching [R502.8, R602.6]	
	☐ Fireblocking & draftstopping [R302.11, R302.12]	

Ш	Radon piping installed & labeled [MN Rules 1303.2402	Building Final Inspection
П	Subp. 5]  Dock lodger pasts beam joists bangers stairs [BE07]	☐ Site address [R319]
	Deck: ledger, posts, beam, joists, hangers, stairs [R507]	☐ Smoke & CO Alarms [R314, R315]
د ا	th Inspection (Adhered Masonry	☐ Guards & handrails [R312.1, R311.7.8]
		☐ Window fall protection [R312.2]
Ve	eneer)	☐ Attic access weatherstripped and insulated [RE402.2.4,
	Water-resistive barrier [R703.7.3, R703.12.3]	Table RE402.4.1.1]
	Lath fastening [R703.7.1]	☐ Gypsum: dwelling-garage separation, under stair
	Flashing, weep screed [R703.4, 703.12.2]	protection, basement ceiling [R302.6, R302.7, R302.13]
	Clearance [703.12.1]	☐ Mechanical Room: 80sf max unprotected and blocked
		to subfloor [R302.13 Exception 3]
In	sulation Inspection	☐ Finishes meet smoke/flame spread requirements [R302.9]
	Air barrier [RE402.4]	☐ Radon system labeled [MN Rules 1303.2402 Subp. 5.E]
	Vapor retarder [R702.7]	☐ Sump pit lid sealed (if used for Radon) [MN Rules
	Insulation: foundation, walls, rim joist, floor, concealed	1303.2402 Subp. 4.E]
	attics, window/door jambs [RE402]	☐ Basement floor slab sealed to foundation wall; other
	Penetrations sealed and/or fireblocked [R302.11, Table	concrete joints sealed. [MN Rules 1303.2402 Subp. 4.B]
	RE402.4.1.1]	☐ Garage/dwelling separation: door, wall/ceiling gypsum
	the transfer of the second	[R302.6]
IVI	echanical Final Inspection	☐ Roof venting [R806]
	Furnace [RE403.5, FG303, FG304, FG306, FG307,	☐ Siding: installed per manufacturer, flashing, distance to
	FG310, FG409.5, FG411, FG503, FG610]	grade [R703.3, R703.4, R317.1]
	Water heater [RE403.4.2, FG303, FG304, FG306,	☐ Deck: decking, guards, handrails, lateral load
_	FG310, FG409.5, FG411, FG503, FG Chapter 5]	connectors [R507]
	A/C unit [RE403.3, RE403.5.17, RE403.6, M307,	☐ Patio door: blocked or guard installed if a deck is not
_	M1101.10]	present [R312]
	Mechanical ventilation, ERV/HRV [RE403.5, M501.3.1]	Final grading [R401.3, R404.1.6]
	Gas fireplace [M501.3.1] Vent terminations, hoods, locations [RE403.5.11,	<ul><li>☐ Energy Compliance Certificate [RE401.3]</li><li>☐ Blower door test [RE402.4.1.2]</li></ul>
_	M401.4, M501.3.1]	☐ Insulation installation certificate [RE303.1.1]
	Intake & exhaust outlets labeled [RE403.5.15]	☐ Required vegetation & landscaping (per local authority
	Gas connections & sediment traps [M408.4, M411.1]	Required hardcover: driveway & sidewalk (per local
	Supply & return air grills [M603.18]	authority)
	ouppry accession on Grand (conserve)	☐ Issuance of Certificate of Occupancy if all items are
Ы	umbing Final	complete [MN Rules 1300.022
	Manometer test [P712.5]	
	Fixtures set [P Chapter 4, P712.5]	Code Section References:
	Dishwasher high loop or air gap [P414.3]	R: 2020 Minnesota Residential Code
	Water hammer devices [P609.10]	
	Water softener: bonding jumper, air gap [P611]	RE: 2015 Minnesota Residential Energy Code
	Shower surround height [R307.2]	P: 2020 Minnesota Plumbing Code
	Water heater [P Chapter 5]	1. 2020 Willinesota Flumbing Code
	Backwater valve accessible [P710.6]	M: 2020 Minnesota Mechanical Code
	Lawn irrigation backflow preventer tested & tagged	FC: 2020 Minnesota Fuel Coe Code
_	[P603.4.2]	FG: 2020 Minnesota Fuel Gas Code
П	Plumbing vent roof caps removed	
Ę1.	ectrical Final Inspection	
	ectrical Final Inspection	
Ш	Verify completion by appropriate authority	

